

PRODUCT SPECIFICATION

Part No.:	AC-QFAOC-8G40-X	
Description:	40G QSFP+ to 4X10G SFP+ Active Optical Cable,MMF 850nm 1-100m	
Release Date	Rev.	Revision Change Description
2016/07/16	A0	New Release
2020/12/28	A1	Template Update

Features

QSFP+ AOC end:

- ✧ Compliant to the 40GBASE-SR4 and XLPP1 Specification per IEEE 802.3ba-2010 and supporting 40G-IB-QDR / 20G-IB-DDR / 10G-IB-SDR applications
- ✧ Compliant to the industry standard SFF-8436 QSFP+ Specification
- ✧ Power Level 1: Max Power < 1.5 W
- ✧ Operate at 10.3125 Gbps per channel with 64b/66b encoded data for 40GbE application and at 10 Gbps with 8b/10b compatible encoded data for 40G-IB-QDR application

Each 4×SFP+ end:

- ✧ Compliant to the electrical specifications per SFF-8431 Specifications for Enhanced Small Form Factor Pluggable Module
- ✧ Mechanical specifications per SFF Committee SFF-8432 Improved Pluggable Form factor “IPF”
- ✧ Maximum power dissipation 0.35W per end
- ✧ Standard: 0~70°C

Application

- ✧ 40GbE and 10GbE break-out applications for Datacom switch and router connections
- ✧ 40G to 4×10G density applications for Datacom and Proprietary protocol applications

Standard

- ✧ Compliant to IEEE 802.3ba
- ✧ Compliant with QSFP+ MSA
- ✧ Compliant to SFF-8436

Specification

Absolute Maximum Ratings				
Parameter	Symbol	Min	Max	Unit
Storage Ambient Temperature	T _{STG}	-40	85	°C
Operating Case Temperature	T _C	0	70	°C
Operating Humidity	H _O	5	85	%
Power Supply Voltage	V _{CC}	-0.3	+3.6	V
Input Voltage	V _{IN}	-0.3	V _{CC} +0.3	V

Recommended Operating Conditions					
Parameter	Symbol	Min	Typical	Max	Unit
Power Supply Voltage	V _{CC}	3.135	3.3	3.465	V
Data Rate,each Lane			10.3125	11.3	Gbps
Data Speed Tolerance	ΔDR	-100		+100	ppm
Link Distance with OM3 fiber	D	0		100	m
Control Input Voltage High		2		V _{CC} +0.3	V
Control Input Voltage Low		-0.3		0.8	V
I2C Serial Interface frequency	f _s			400k	Hz
Power Supply Noise				50	mVpp
Receiver Differential Data Output Load				100	mVpp

The following electrical characteristics are defined over the Recommended Operating temperature and supply voltage unless otherwise specified.						
Parameter	Symbol	Min	Typical	Max	Unit	Notes
QSFP+40G Active Cable-End Power Consumption				1.5	W	
QSFP+40G Active Cable-End Power Supply Current				300	mA	
SFP+ 10G Active Cable-End Power Consumption				0.35	W	
SFP+ 10G Active Cable-End Power Supply Current				100	mA	

QSFP+AOC-end Electrical Characteristics Electrical Specifications

Parameter	Symbol	Min	Typical	Max	Unit	Notes
Differential input impedance	Zin	90	100	110	ohm	
Differential Output impedance	Zout	90	100	110	ohm	
Differential input voltage amplitude	ΔV_{in}	300		1100	mVp-p	
Differential output voltage amplitude	ΔV_{out}	400		800	mVp-p	
Bit Error Rate	BR			E-12		
Input Logic Level High	V _{IH}	2.0		VCC	v	
Input Logic Level Low	V _{IL}	0		0.8		
Output Logic Level High	V _{OH}	VCC-0.5		VCC	v	
Output Logic Level Low	V _{OL}	0		0.4	v	


QSFP+ AOC-end Pin Descriptions

Pin	Symbol	Name/Description	Logic	Note
1	GND	Ground		1
2	Tx2n	Transmitter Inverted Data Input	CML-I	
3	Tx2p	Transmitter Non-Inverted Data output	CML-I	
4	GND	Ground		1
5	Tx4n	Transmitter Inverted Data Input	CML-I	
6	Tx4p	Transmitter Non-Inverted Data output	CML-I	
7	GND	Ground		1
8	ModS _{EL}	Module Select	LVTTLL-I	
9	ResetL	Module Reset	LVTTLL-I	
10	VccRx	+ 3.3V Power Supply Receiver		2
11	SCL	2-Wire Serial Interface Clock	LVC MOS-I/O	
12	SDA	2-Wire Serial Interface Data	LVC MOS-I/O	
13	GND	Ground		
14	Rx3p	Receiver Non-Inverted Data Output	CML-O	
15	Rx3n	Receiver Inverted Data Output	CML-O	
16	GND	Ground		1
17	Rx1p	Receiver Non-Inverted Data Output	CML-O	
18	Rx1n	Receiver Inverted Data Output	CML-O	
19	GND	Ground		1
20	GND	Ground		1
21	Rx2n	Receiver Inverted Data Output	CML-O	
22	Rx2p	Receiver Non-Inverted Data Output	CML-O	

23	GND	Ground		1
24	Rx4n	Receiver Inverted Data Output	CML-O	1
25	Rx4p	Receiver Non-Inverted Data Output	CML-O	
26	GND	Ground		1
27	ModPrsL	Module Present	LVTTTL-O	
28	IntL	Interrupt	LVTTTL-O	
29	VccTx	+3.3 V Power Supply transmitter		2
30	Vcc1	+3.3 V Power Supply		2
31	LPMODE	Low Power Mode	LVTTTL-I	
32	GND	Ground		1
33	Tx3p	Transmitter Non-Inverted Data Input	CML-I	
34	Tx3n	Transmitter Inverted Data Output	CML-I	
35	GND	Ground		1
36	Tx1p	Transmitter Non-Inverted Data Input	CML-I	
37	Tx1n	Transmitter Inverted Data Output	CML-I	
38	GND	Ground		1

Notes:

- 1) Module circuit ground is isolated from module chassis ground within the module. GND is the symbol for signal and supply (power) common for QSFP modules.
- 2) The connector pins are each rated for a maximum current of 500mA.



ModSelL Pin

The ModSelL is an input pin. When held low by the host, the module responds to 2-wire serial communication commands. The ModSelL allows the use of multiple QSFP modules on a single 2-wire interface bus. When the ModSelL is “High”, the module will not respond to any 2-wire interface communication from the host. ModSelL has an internal pull-up in the module.

ResetL Pin

Reset. LPMoDe_Reset has an internal pull-up in the module. A low level on the ResetL pin for longer than the minimum pulse length (t_{Reset_init}) initiates a complete module reset, returning all user module settings to their default state. Module Reset Assert Time (t_{init}) starts on the rising edge after the low level on the ResetL pin is released. During the execution of a reset (t_{init}) the host shall disregard all status bits until the module indicates a completion of the reset interrupt. The module indicates this by posting an IntL signal with the Data_Not_Ready bit negated. Note that on power up (including hot insertion) the module will post this completion of reset interrupt without requiring a reset.

LPMoDe Pin

LONTE QSFP+ SR4 operate in the low power mode (less than 1.5 W power consumption) This pin active high will decrease power consumption to less than 1W.

ModPrsL Pin

ModPrsL is pulled up to Vcc on the host board and grounded in the module. The ModPrsL is asserted “Low” when the module is inserted and deasserted “High” when the module is physically absent from the host connector.

IntL Pin

IntL is an output pin. When “Low”, it indicates a possible module operational fault or a status critical to the host system. The host identifies the source of the interrupt by using the 2-wire serial interface. The IntL pin is an open collector output and must be pulled up to Vcc on the host board.

QSFP+ AOC-end Power Supply Filtering

The host board should use the power supply filtering shown in Figure1.




Figure1. Host Board Power Supply Filtering

QSFP+ AOC-end EEPROM Serial ID Memory Contents:

Compliant to the industry standard SFF-8436 QSFP+ Specification

SFP+ AOC-end Electrical Specifications

Parameter	Symbol	Min	Typical	Max	Unit
Differential input impedance	Zin	90	100	110	ohm
Differential Output impedance	Zout	90	100	110	ohm
Differential input voltage amplitude aAmplitude	Δ Vin	100		1800	mVp-p
Differential output voltage amplitude	Δ Vout	400		800	mVp-p
Bit Error Rate	BR			E-12	
Input Logic Level High	VIH	2.0		VCC	V
Input Logic Level Low	VIL	0		0.8	V

SFP+ AOC-end Pin Descriptions

Pin	Symbol	Name/Description	Note
1	VeeT	Transmitter Signal Ground	1
2	TX_FAULT	Transmitter Fault (LVTTTL-O) – Not used. Grounded inside the module	2
3	TX_DISABLE	Transmitter Disable (LVTTTL-I) – High or open disables the transmitter	3
4	SDA	Two Wire Serial Interface Data Line (LVCMOS – I/O) (same as MOD-DEF2 in INF-8074)	4
5	SCL	Two Wire Serial Interface Clock Line (LVCMOS – I/O) (same as MOD-DEF1 in INF-8074)	4
6	MOD_ABS	Module Absent (Output), connected to VeeT or VeeR in the module	5
7	RS0	Rate Select 0 - Not used, Presents high input impedance	
8	RX_LOS	Receiver Loss of Signal (LVTTTL-O)	2
9	RS1	Rate Select 1 - Not used, Presents high input impedance	
10	VeeR	Receiver Signal Ground	1
11	VeeR	Receiver Signal Ground	1
12	RD-	Receiver Data Out Inverted (CML-O)	
13	RD+	Receiver Data Out (CML-O)	
14	VeeR	Receiver Signal Ground	
15	VccR	Receiver Power + 3.3 V	
16	VccT	Transmitter Power + 3.3 V	
17	VeeT	Transmitter Signal Ground	1
18	TD+	Transmitter Data In (CML-I)	
19	TD-	Transmitter Data In Inverted (CML-I)	
20	VeeT	Transmitter Signal Ground	1

Notes:

- 1) Module circuit ground is isolated from module chassis ground within the module. GND is the symbol for signal and supply (power) common for SFP modules.
- 2) This is an open collector/drain output that on the host board requires a 4.7 kΩ to 10 kΩ pull up resistor to Vcc Host. See Figure 2.
- 3) This input is internally biased high with a 4.7 kΩ to 10 kΩ pull up resistor to VccT.
- 4) Two-Wire Serial interface clock and data lines require an external pull up resistor dependent on the capacitance load.
- 5) This is a ground return that on the host board requires a 4.7 kΩ to 10 kΩ pull up resistor to Vcc Host.





Figure 2




QSFP+ AOC-end Power Supply Filtering



NOTE: INDUCTORS MUST HAVE LESS THAN 1Ω SERIES RESISTANCE TO LIMIT VOLTAGE DROP TO THE SFP MODULE.

SFP+ AOC end Mechanical Specifications

Dimensions are in millimeters. All dimensions are $\pm 0.2\text{mm}$ unless otherwise specified.(unit: mm)



ESD

This transceiver is specified as ESD threshold 1kV for Signal pads and 2kV for all others electrical input pads, tested per MIL-STD-883, Method 3015.4 /JESD22-A114-A (HBM). However, normal ESD precautions are still required during the handling of this module. This transceiver is shipped in ESD protective packaging. It should be removed from the packaging and handled only in an ESD protected environment.

Laser Safety

This is a Class 1 Laser Product according to IEC 60825-1:2007. This product complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50.

Regulatory Compliance

Feature	Test	Method
Electrostatic Discharge (ESD) to the Electrical Pins	MIL-STD-883E Method 3015.7	Class 1(>1000V for SFI pins, >2000Vfor other pins.)
Electrostatic Discharge (ESD) Immunity	IEC61000-4-2	Class 2(>4.0kV)
Electromagnetic Interference (EMI)	CISPR22 ITE Class B FCC Class B CENELEC EN55022 VCCI Class 1	Comply with standard
Immunity	IEC61000-4-3	Comply with standard
Eye Safety	FDA 21CFR 1040.10 and 1040.11 EN (IEC) 60825-1,2	Compatible with Class I laser Product

Order Information

Part Number	Product Description
AC-QFAOC-8G40-X	40G QSFP+ to 4x10G SFP+ Active Optical Cable 1-100m

Notes:

Where "x" denotes cable length in meters. Examples are as follows:

x = 03 for 3m, x = 10 for 10m, x = 50 for 50m, x = A0 for 100m.